

(12) UK Patent Application (19) GB (11) 2 361 310 (13) A

(43) Date of A Publication 17.10.2001

(21) Application No 0100079.3

(22) Date of Filing 03.01.2001

(30) Priority Data

(31) 60174434

(32) 04.01.2000

(33) US

(71) Applicant(s)

Lear Corporation

(Incorporated in USA - Delaware)

21557 Telegraph Road, Southfield, Michigan 48034,
United States of America

(72) Inventor(s)

Robert H Wilson

(74) Agent and/or Address for Service

Urquhart-Dykes & Lord

New Priestgate House, 57 Priestgate,
PETERBOROUGH, PE1 1JX, United Kingdom

(51) INT CL⁷

E05F 15/00

(52) UK CL (Edition S)

G1A AA3 AG17 AG9 AMQM AMQX AR6 AT25 AT27
G1G GPE

(56) Documents Cited

GB 2342714 A DE 004321028 A1 DE 004028584 A1
FR 002685503 A1 JP 110270229 A US5069000 A

(58) Field of Search

UK CL (Edition S) E2M MAB, G1A AMQM AMQX,
G1G GPE
INT CL⁷ E05F 15/00, F16P 3/14, G01D 5/34, G01V
8/12 8/14 8/20 8/22
ONLINE: EPODOC, WPI, JAPIO

(54) Abstract Title

Optoelectronic system for an automatic vehicle door closure

(57) A non-contact optoelectronic system for an automatic vehicle door closure detects the presence of an obstruction. The non-contact optoelectronic system includes at least one transmitter (30) for emitting an electromagnetic energy signal (32) and at least one sensor (34) for detecting the electromagnetic energy signal (32) emitted by the transmitter (30). A control module (38) in communication with the transmitter (30) and sensor (34) monitors and processes the signal interrupts detected by the sensor (34) to sense an obstruction between the transmitter (30) and sensor (34). The control module (38) generates a motor control signal to stop and open a vehicle door (22) upon detection of an obstruction between the transmitter (30) and sensor (34). In a second embodiment mirrors, polished metal or reflective surfaces are disposed on the inner surfaces of the door and door jamb to allow electromagnetic energy emitted by a transmitter to reflect between the vehicle door and door jamb. Preferably the electromagnetic energy in either embodiment is infrared energy to eliminate undesired effects from ambient light. Instead of electromagnetic energy, the system may also use ultrasound energy.




Fig. 1

At least one drawing originally filed was informal and the print reproduced here is taken from a later filed formal copy.

This print takes account of replacement documents submitted after the date of filing to enable the application to comply with the formal requirements of the Patents Rules 1995

GB 2 361 310 A




Fig. 1




Fig. 2





Fig. 3

*Fig. 4*

OPTOELECTRONIC SYSTEM FOR AN AUTOMATIC VEHICLE DOOR CLOSURE

BACKGROUND OF THE INVENTION

1. Field of the Invention

5 The present invention relates to a non-contact optoelectronic system for an automatic vehicle door closure and more particularly to an infrared anti-pinch system for sensing obstructions between a closing vehicle door and a door jamb.

2. Background Art

10 Certain modern minivans and other vehicles are equipped with automatic sliding doors. The automatic sliding doors include a "one-touch" closing feature, wherein a single touch of a control button on the vehicle door or instrument panel actuates the motor assembly to automatically close the door. These minivans typically include an obstruction detection system, which senses the presence of an object in the path of the automatic vehicle door. The obstruction detection system
15 is coupled to a motor control device which sends a signal to the door motor drive to cease the automatic forward progress, and, in some cases, reverse the direction of the door to allow an operator to remove the obstruction from the door path.

 One known obstruction detection system senses an obstruction between the closing door and the door jamb by sensing current surges in the drive
20 motor. The system generates a door position signal for a predetermined distance of door movement to measure door speed. The system establishes an obstruction by measuring the stall time of the drive motor. For example, if a toy is caught between the door and the door jamb, the drive motor current will surge as the toy is engaged, and this current surge will be detected by a control module, which
25 signals the door to open. A problem with this type of system is that the sensing of a motor surge requires that a certain amount of force be applied to the pinched

object, which may cause serious trauma to an individual even though the door is eventually reversed.

5 An alternative obstruction detection system for a van door closure system includes a pressure sensor coupled to one or both edges of the vehicle door and door jamb to sense the presence of an object adjacent the door or door jamb. A typical pressure sensor system includes an elongated electrical cable or mechanism having a pair of wires disposed within the cable. As the door or door jamb encounters an obstacle, the wires in the cable are brought into contact, sending a signal to the motor control to stop the forward progress of the motor and to
10 reverse the direction of the door. Similarly to the current detection system, the pressure sensor obstruction detection system requires a certain amount of force be applied to the pinched object causing serious trauma to an individual or object.

Accordingly, it is desirable to provide a non-contact optoelectronic system for a van door closure and a method of preventing pinching by an automatic
15 sliding vehicle door that does not incorporate a mechanical or electromechanical sensing mechanism which contacts the obstruction prior to reversing direction and/or which provides improvements generally

SUMMARY OF THE INVENTION

According to the invention there is provided systems and methods as defined in the accompanying claims.

20 It is a desirable object of the invention to provide a non-contact optoelectronic system for automatic vehicle door closure which prevents and object from becoming trapped between the vehicle door and the door jamb.

Another desirable object of the invention is to provide a non contact optoelectronic system for an automatic vehicle door closure using optical wave transmitters and sensors coupled to a control module to prevents the obstruction from being lodged between the door and door jamb.

25 A further desirable object of the invention is to provide a non-contact optoelectronic system for an automatic vehicle door closure and a door jamb using an optical wave transmitter and sensor in combination with reflective material

disposed on the door and door jamb coupled to a control module to prevent an object from becoming trapped between the vehicle door and the door jamb.

Yet another desirable object of the invention is to provide a method of detecting an obstruction between a door and door jamb which does not require contact between the obstruction and the door or door jamb.

An embodiment of the present invention addresses the above-referenced shortcomings of prior art automatic sliding door assemblies by providing a non-contact optoelectronic system for automatic vehicle door closure and a method of detecting an obstruction in an automatic vehicle door closure system. The non-contact optoelectronic system comprises at least one transmitter for transmitting an electromagnetic energy signal and at least one sensor for detecting the electromagnetic signal during the automatic closing of the vehicle door. A control module is in communication with the at least one transmitter and at least one sensor and receives a signal from the at least one sensor. A control module processes the signal from the at least one sensor and generates a motor control signal to stop and reverse the vehicle door upon detection of an obstruction between the at least one transmitter and at least one sensor.

In a first embodiment of the invention, the non-contact optoelectronic system includes a pair of transmitters disposed on an inner surface of a vehicle door which emit an electromagnetic energy interrupt signal, such as an infrared light signal. A plurality of array of sensors are mounted on an inner surface of a door jamb of a vehicle to detect the electromagnetic energy signals emitted by the transmitters. A control module in communication with the transmitters and the sensors activates the transmitters and sensors upon receiving a signal from a switching mechanism to close the automatic vehicle door. The control module sends a signal to the drive motor to move the automatic vehicle door into position.

The control module monitors the signal interrupts detected by the sensors to sense an obstruction between the door and the door jamb during the forward travel of the vehicle door. The control module processes the signals

received from the array of sensors and compares the interrupts detected by the sensors against stored values to determine whether an obstruction is present between the door and door jamb. If an obstruction is detected between the vehicle door and door jamb, the control module transmits a signal to a drive motor to open the vehicle door and return the door to a manual operating mode.

In a second embodiment of the invention, the non-contact optoelectronic system includes a transmitter disposed on an inner surface of a vehicle door which emits an electromagnetic energy interrupt signal, such as an infrared light signal. A plurality or array of sensors are mounted on an inner surface of a door jamb of a vehicle to detect the signal emitted by the transmitter. Alternatively, a single sensor may be mounted to an inner surface of the door jamb to detect the signals emitted by the transmitter.

A first reflective surface is disposed on an inner surface of the vehicle door and a second reflective surface is disposed on an inner surface of the door jamb. The reflective surfaces allow the electromagnetic energy signal emitted by the transmitter to reflect between the vehicle door and door jamb. Reflective surfaces may be polished portions of the substrate of the door and door jamb, a reflective coating applied to the inner surfaces of door and door jamb, or a polished metal foils disposed on the door and door jamb.

A control module in communication with the transmitter and the array of sensors monitors the signal interrupts detected by the sensors to sense an obstruction between the door and the door jamb during the forward travel of the vehicle door. The control module processes the signals against stored comparison values to determine whether an obstruction appears between the door and door jamb. If an obstruction is detected between the vehicle door and door jamb, the control module transmits a signal to a drive motor to reverse the vehicle door travel and return the door to a manual operating mode.

A method of detecting an obstruction for an automatic vehicle door closure systems is also disclosed. A non-contact optoelectronic system is provided

to monitor an area between the door and door jamb. The non-contact optoelectronic system includes at least one transmitter disposed on an inner surface of the vehicle door to transmit an electromagnetic energy signal and at least one sensor mounted on an inner surface of the door jamb to detect the electromagnetic energy signal.

5 The at least one sensor transmits the received electromagnetic energy signal to a control module in communication with the at least one transmitter and at least one sensor.

A control module monitors electromagnetic energy interrupt signals detected by at least one sensor. The control module processes the signal by

10 comparing the interrupts generated by the at least one sensor to stored values to detect the presence of an obstruction between the door and door jamb. If an obstruction is detected, the control module transmits a signal to the drive motor to open the automatic door. The method further comprises a hardware fault detection system which sends a pulse of infrared light from the at least one transmitter to the

15 at least one sensor to test the non-contact optoelectronic system during the rearward travel or opening of the automatic vehicle door closure system.

The above objects and other objects, features and advantages of the present invention are readily apparent from the following detailed description of the

20 best mode for carrying out the invention when taken in connection with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIGURE 1 is front plan view of an automatic vehicle door closure assembly including the non-contact optoelectronic system of the present invention;

25 FIGURE 2 is a schematic view of a first embodiment of the non-contact optoelectronic system of the present invention;

FIGURE 3 is a schematic view of a second embodiment of the non-contact optoelectronic system in accordance with the present invention; and

FIGURE 4 is a block diagram of the method of detecting an obstruction in an automatic vehicle door closure system of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT(S)

Referring now to the Figures, an automatic vehicle door closure having a non-contact optoelectronic system is disclosed. As is shown in Figure 1, a vehicle 10 includes a vehicle body 12 including a entry area or passage 14 leading to an interior passenger compartment of the vehicle 10. A door jamb 16 extends about the inner periphery of passage 14 in vehicle body 12. The door jamb 16 includes a striker, shown generally as numeral 18, which is received by a latch 20 mounted on a sliding vehicle door 22. Vehicle door 22 is horizontally adjustable, as is represented by numeral 24, between an open position and a closed position adjacent passage 14 to allow occupants access to and from the passenger compartment of the vehicle. Latch 20 engages striker 18 on door jamb 16 to secure sliding vehicle door 22 in position adjacent passage 14 in vehicle body 12. A motor is coupled to the vehicle door 22 to automatically close the door upon activation of a switch by the operator.

Referring now to Figures 2 and 3, a non-contact optoelectronic system of the present invention is described in greater detail. Non-contact optoelectronic system is disposed on the inner surface 26 of sliding vehicle door 22 and the inner surface 28 of door jamb 16 to ensure that an obstruction, such as a limb of an occupant or object, is not trapped or lodged between the door 22 and jamb 16 during the automatic door closing. Non-contact optoelectronic system includes at least one transmitter for emitting an electromagnetic energy signal and at least one sensor for detecting the electromagnetic energy signal emitted by the at least one transmitter. The at least one transmitter is disposed on the inner surface 26 of the vehicle door 22. The at least one transmitter emits an electromagnetic energy signal 32 towards the door jamb 16. At least one sensor is mounted on the inner surface 28 of door jamb 16 and detects signals from the at least one transmitter. It is also understood that transmitters may be disposed on the inner surface 28 of door jamb 16 while sensors are mounted on the inner surface 26 of

vehicle door 22 to provide an alternative arrangement for non-contact optoelectronic system 24.

5 A control module is provided in communication with the at least one transmitter and at least one sensor for monitoring the electromagnetic energy signal interrupts detected by the at least one sensor. The control module processes the electromagnetic energy signals to sense an obstruction between the at least one transmitter on the vehicle door 22 and the at least one sensor on the inner surface of the door jamb 16. The control module generates a motor control signal to open the vehicle door 22 upon detection of an obstruction between the at least one
10 transmitter and at least one sensor.

Referring now to Figure 2, a first embodiment of the non-contact optoelectronic system of the present invention is shown. Non-contact optoelectronic system 24 includes a pair of transmitters 30 mounted in the sliding vehicle door 22. Each transmitter 30 includes a transmitting portion 36 extending outward of or
15 through an aperture in the inner surface 26 of door 22. Each transmitting portion 36 emits a signal 32 towards the door jamb 16. A plurality of sensors 34 are positioned in an array on the inner surface 28 of door jamb 16 to detect the signal 32 emitted from transmitters 30. The plurality of sensors 34 are preferably mounted on the inner surface 28 of door jamb 16 as an array to provide a broad
20 spectrum of detection for signals 32 emitted by transmitters 30.

By way of example, the transmitters 30 may emit electromagnetic energy signals such as infrared light signal interrupts in the form of square waves having 1 KHz wavelength. Alternatively, an ultrasound wave could be implemented to generate the signal interrupts detected by sensors 34. The plurality or array of
25 sensors 34 detect the infrared light 32 to determine the wavelength of the detected infrared light to develop an interrupt pattern. It is advantageous to use infrared transmitters in combination with the array of sensors 34, eliminating the need to specifically align the transmitter and sensor to monitor a region for obstructions. Additionally, the array of sensors 34 will not be affected by ambient light or

sunlight and thus do not cause false obstruction readings for the non-contact optoelectronic system.

5 A control module 38 is in communication with the transmitters 30 and sensors 34 disposed on vehicle door 22 and door jamb 16 by connections, schematically shown as numeral 40. The control module 38 monitors the signal interrupts detected by sensors 34 sent by transmitters 30. The control module 38 is additionally in communication with a switching mechanism 42 and drive motor 44 to control the automatic opening and closing of the vehicle door 22.

10 To operate the automatic vehicle door closure system, an operator activates automatic vehicle door 22 by depressing switch mechanism 42. Switch mechanism 42 signals control module 38 to activate drive motor 44. Drive motor 44 moves sliding vehicle door 22 along a track in the vehicle body towards door jamb 16. At the same time, control module 38 activates transmitters 30 and sensors 34 to monitor the horizontal forward progress of the transmitter and sensors on the door 22 toward door jamb 16. Control module 38 monitors the interrupts generated by transmitters 30 using sensors 34 to detect the presence of any obstructions between the door 22 and door jamb 16 during the forward travel of the door.

20 The control module 38 compares the interrupts detected by sensors 34 against stored values to determine whether an obstruction exists between the door 22 and door jamb 16. When the sensors 34 detect wavelength changes in the emitted infrared light 32, it is assumed that an obstruction is positioned between the moving door 22 and the door jamb 16. If the control module 38 determines the changes in wavelength detected by the sensors 34 do not match the stored values, then the control module 38 generates and sends a "door open" signal to the drive motor 44 to halt forward progress of door 22. The control module 38 additionally sends a signal to reverse the door travel to prevent the obstruction from being trapped or lodged between the door 22 and door jamb 16.

Referring now to Figure 3, a second embodiment of the non-contact optoelectronic system of the present invention is shown. Non-contact optoelectronic

Upon receipt of this signal from switching mechanism, the microprocessor of control module sends a signal to the drive motor to initiate the forward travel and closing of the vehicle door. Control module further activates the non-contact optoelectronic system at block 84, activating the transmitter to emit an electromagnetic energy interrupt signal and the sensors to detect the signals.

The microprocessor of control module monitors interrupts from input capture ports 86 of the sensors. The microprocessor is programmed to allow the door to continue forward travel to close if an expected number of interrupts occur to indicate that the door is unobstructed until the next software cycle. The software program includes predetermined stored values for expected signal rates and times during the forward travel of the door, which are compared to the signals from the sensors. If the software program run by the microprocessor does not detect a specific number of interrupts programmed to occur in a time interval, shown at block 88, the microprocessor will assume an obstruction exists between the door and door jamb.

The microprocessor of control module will then stop the "one-touch" door closing operation by processing and sending a signal 90 to the drive motor to stop the forward travel to open the vehicle door. Additionally, the door will be opened a determined distance and will return to a manual mode of operation 92. The microprocessor may also initiate a signal to chime an alarm to warn the driver of an obstruction. If the control module senses a set number of interrupts in a time interval, shown at block 94, then the sliding vehicle door will continue its forward travel towards door jamb until the door is placed in a closed position 96.

While embodiments of the invention have been illustrated and described, it is not intended that these embodiments illustrate and describe all possible forms of the invention. Rather, the words used in the specification are words of description rather than limitation, and it is understood that various changes may be made without departing from the spirit and scope of the invention.

WHAT IS CLAIMED IS:"

1 1. A non-contact optoelectronic system for an automatic vehicle
2 door closure to detect the presence of an obstruction, the system comprising:
3 at least one transmitter for emitting an electromagnetic energy signal;
4 at least one sensor for detecting the electromagnetic energy signal
5 emitted by the at least one transmitter;
6 a control module in communication with the at least one transmitter
7 and at least one sensor for monitoring and processing the signal interrupts detected
8 by the at least one sensor to detect an obstruction between the at least one
9 transmitter and at least one sensor, wherein the control module generates a motor
10 control signal to stop and/or reverse a vehicle door upon detection of an
11 obstruction between the at least one transmitter and at least one sensor.

1 2. The optoelectronic system of claim 1 wherein the control
2 module processes the electromagnetic energy signal interrupts from the at least one
3 sensor by comparing the interrupts against stored values to determine whether an
4 obstruction is present in an entry area of the vehicle.

1 3. The optoelectronic system of claim 1 or 2 wherein the entry area
2 of the vehicle is defined by a passage in a vehicle body, a door jamb defining an
3 outer periphery of the passage and a vehicle door selectively positionable between
4 an open position and a closed position adjacent the passage of the vehicle.

1 4. The optoelectronic system of any preceding claim wherein the
2 at least one transmitter further comprises a pair of transmitters disposed on an
3 inner surface of the vehicle door.

1 5. The optoelectronic system of any preceding claim wherein the
2 at least one sensor further comprises a single sensor disposed on an inner surface
3 of the door jamb.

1 6. The optoelectronic system of any preceding claim wherein the
2 at least one sensor further comprises a plurality of sensors disposed on the inner
3 surface of the door jamb.

1 7. The optoelectronic system of claim 6 wherein the plurality of
2 sensors are arranged as an array on the inner surface of the door jamb to detect
3 signals transmitted by the at least one transmitter.

1 8. The optoelectronic system of any preceding claim further
2 comprising a first reflective surface disposed on the inner surface of the vehicle
3 door and a second reflective surface disposed in the inner surface of the door
4 jamb to reflect the emitted signal from the at least one transmitter to the at least
one sensor.

1 9. The optoelectronic system of claim 8 wherein the first and
2 second reflective surfaces comprise a reflective coating applied to the inner surfaces
3 of the vehicle door and door jamb.

1 10. The optoelectronic system of claim 8 wherein the first and
2 second reflective surfaces comprise a polished metal surface disposed on the inner
3 surfaces of the vehicle door and door jamb.

1 11. The optoelectronic system of any preceding claim wherein the
2 electromagnetic energy signal emitted by the at least one transmitter is infrared
3 light.

1 12. An automatic vehicle door closure system comprising:
2 an entry area for a vehicle, the entry area defined by a passage in a
3 vehicle body, a door jamb defining an outer periphery of the passage and a vehicle
4 door selectively positionable between an open position and a closed position
5 adjacent the passage of the vehicle;
6 a drive motor operatively connected to the motor for selectively
7 positioning the door between an open and closed position;

8 at least one transmitter for emitting an electromagnetic energy signal
9 into the entry area of the vehicle;
10 at least one sensor for detecting the electromagnetic energy signal
11 emitted by the at least one transmitter in the entry area of the vehicle;
12 a control module in communication with the at least one transmitter
13 and at least one sensor for monitoring and processing the signal interrupts detected
14 by the at least one sensor to sense an obstruction in the entry area of the vehicle
15 during the closing of the vehicle door, wherein the control module generates and
16 sends a motor control signal to the motor to stop and/or open the vehicle door
17 upon detection of an obstruction between the at least one transmitter and at least
18 one sensor in the entry area of the vehicle.

1 13. The vehicle door closure system of claim 12 wherein the
2 control module compares the interrupts detected by the at least one sensor against
3 stored values to determine whether an obstruction is present in the entry area of the
4 vehicle.

1 14. The vehicle door closure system of claim 12 or 13 wherein the
2 control module activates the at least one transmitter and at least one sensor upon
3 receiving a signal from a switching mechanism to operate drive motor to close the
4 vehicle door.

1 15. The vehicle door closure system of anyone of claims 12 to 14
2 wherein the at least one transmitter further comprises a pair of transmitters
3 disposed on an inner surface of the vehicle door.

1 16. The vehicle door closure system of anyone of claims 12 to 14
2 wherein at least one sensor further comprises a plurality of sensors disposed on
3 the inner surface of the door jamb.

1 17. The vehicle door closure system of claim 16 wherein the
2 plurality of sensors are arranged as an array on the inner surface of the door jamb
3 to detect signals transmitted by the at least one transmitter.

1 18. The vehicle door closure system of anyone of claims 12 to 18
2 wherein the electromagnetic energy signal emitted by the at least one transmitter
3 is infrared light.

1 19. A method of detecting an obstruction in an automatic vehicle
2 door closure, the method comprising the steps of:
3 providing a non-contact optoelectronic system for detecting the
4 presence of an obstruction during the closing of the vehicle door, the non-contact
5 optoelectronic system including at least one transmitter disposed on an inner surface
6 of a vehicle door, at least one sensor disposed on an inner surface of a door jamb
7 and a control module in communication with the non-contact optoelectronic system;
8 activating the at least one transmitter and at least one sensor when the
9 control module initiates the forward travel of the automatic vehicle door;
10 emitting an electromagnetic energy interrupt signal from the at least
11 one transmitter;
12 detecting the electromagnetic energy interrupt signal emitted from the
13 at least one transmitter with the at least one sensor;
14 monitoring the electromagnetic energy signal interrupts detected by
15 the at least one sensor with the control module for the presence of obstructions
16 between the inner surface of the vehicle door and the inner surface of the door
17 jamb; and
18 processing a signal from the control module to a drive motor
19 operatively connected to the vehicle door to terminate the closing of the door based
20 upon detection of an obstruction between the vehicle door and door jamb.

1 20. The method of claim 19 further comprising the step of
2 comparing the electromagnetic energy signal interrupts detected by the at least one
3 sensor to stored values in the control module to detect the presence of an obstruction
4 between the vehicle door and door jamb.

1 21. The method of claim 19 wherein the step of emitting an
2 interrupt signal from the at least one transmitter further comprises emitting an
3 infrared light signal from the at least one transmitter.

1 22. The method of claim 19 further comprising the step of
2 performing a hardware fault detection of the obstruction detection during the
3 opening of the automatic vehicle door.

1 23. The method of claim 22 wherein the step of performing a
2 hardware fault detection of the non-contact optoelectronic system further comprises
3 sending a pulse of infrared light from the at least one transmitter to the at least one
4 sensor to test the optoelectronic system.

 24. A system as hereinbefore described with reference to
the accompanying figures.

 25. A method as hereinbefore described with reference to
the accompanying figures.



Application No: GB 0100079.3
Claims searched: 1 to 25

Examiner: Andrew Courtenay
Date of search: 8 August 2001

Patents Act 1977 Search Report under Section 17

Databases searched:

UK Patent Office collections, including GB, EP, WO & US patent specifications, in:

UK Cl (Ed.S): G1A (AMQM, AMQX), E2M (MAB), G1G (GPE)

Int Cl (Ed.7): E05F 15/00, F16P 3/14, G01D 5/34, G01V 8/12, 8/14, 8/20, 8/22

Other: ONLINE: EPODOC, WPI, JAPIO.

Documents considered to be relevant:

Category	Identity of document and relevant passage	Relevant to claims
X	GB 2342714 A (MEMCO) See abstract and fig 1 especially	1-7, 11-14 and 18 to 21 at least
A	US 5069000 A (ZUCKERMAN)	-
X	DE 4321028 A1 (KESSLER) See abstract and fig 1a	1 and 12 at least
X	DE 4028584 A1 (HEISS) See abstract and fig 2	1 and 12 at least
X	FR 2685503 A1 (FRANCE DESIGN) See abstract and fig 1	1 and 12 at least
X	JP 11-270229 A (ASMO) See abstract and fig 3 especially	1 and 12 at least

X Document indicating lack of novelty or inventive step
Y Document indicating lack of inventive step if combined with one or more other documents of same category.

& Member of the same patent family

A Document indicating technological background and/or state of the art.
P Document published on or after the declared priority date but before the filing date of this invention.

B Patent document published on or after, but with priority date earlier than, the filing date of this application.